

FREWITT 

# EASYMILL CRUSHER CC-2

MORE THAN A CRUSHER



WE  
CARE  
ABOUT  
MILLING

[WWW.FREWITT.COM](http://WWW.FREWITT.COM)



This technology is patented and owned by Frewitt. Any infringement of our rights will be subject to immediate legal action.

# EASYMILL CRUSHER CC-2

Over the years, Frewitt has proven itself as the market leader in the field of powder milling machines. In its factories, Frewitt develops and produces high-quality mills. Frewitt is the ideal and most qualified partner for your solutions, our broad spectrum of competence will cover all your needs.

## WHY CHOOSE FREWITT?

1

Provides solutions to your problems of line blockages, during production, due to hard and large blocks

2

Solutions that will optimize your production time and increase the quality of grinding

3

Optimized investment with anticipation of your future needs

4

Designed to ensure your safety

5

Machine developed with our commitment  
**FREWITT CARES ABOUT YOU**

## ADDED-VALUE

Module



- Unique solution on the market with crushing zone covering the entire discharge surface
- Simplified disassembly, assembly and cleaning
- Compact assembly for easy in-line integration
- Module or complete machine

Machine



- Possibility to mill with a high throughput
- Compatible with all Frewitt machines
- Integrated system to avoid product bridging
- High-tech process bearing
- Fixation of the module either directly by the frame or supported by the motor



## SUITABLE FOR THE FOLLOWING INDUSTRIES:



Pharmaceutical



Battery



Chemical



Food


## PROCESS CHARACTERISTICS




**Maximum product size at the inlet**  
150mm



**Throughput**  
10 to 8000 kg/h



**Temperature range of product**  
-20°C to +60°C



**Product density**  
up to 2.5 kg/dm<sup>3</sup>

## TECHNICAL CHARACTERISTICS



### Materials

AISI 316/316L - Ra ≤ 0.8 μm  
AISI 304/304L - Ra ≤ 1.4 μm  
EPDM/PTFE/Silicone

Interior  
Exterior  
In product contact,  
certified FDA



### Dimensions & weight

#### Module

Length 710 mm  
Width 420 mm  
Height 440 mm  
Weight 110 kg

#### Machine

Length 1400 mm  
Width 870 mm  
Height 1900 mm  
Weight 280 kg

Diameter DN250



### Standard

GMP  
Sealed process  
Speed control  
High throughput  
Integrated  
bridge-breaker



### Optional

Bearing temperature  
measure  
Ventilated bearing  
Specific custom tooling  
ATEX  
WIP  
SIP



WORLDWIDE PRESENCE



FREWITT HEADQUARTERS

**Frewitt manufacturer of machines Ltd.**  
Route du Coteau 7  
1763 Granges-Paccot  
Switzerland

**Postal address**  
P.O. Box  
1701 Fribourg  
Switzerland

P: +41 26 460 74 00  
info@frewitt.com  
www.frewitt.com

**Frewitt Pharma Machinery  
(China) Co. Ltd.**  
1029 Shenfu Road,  
Xinzhuan Industrial Zone  
201108 Shanghai  
China

P: +86 21 548 32950  
info@frewitt-china.cn  
www.frewitt-china.cn

**Frewitt USA, Inc.**  
249 Homestead Road,  
Building 5, Unit 8  
Hillsborough, NJ 08844  
USA

P: +1 908 829 5245  
info@frewitt-usa.com  
www.frewitt-usa.com